

TEC/SPEC/10-007 Date Established: 08-Oct-10

# **TECHNICAL SPECIFICATION**

## NIPPON ODOUR-LESS EASYWASH

**Description** Nippon Odour-less EasyWash is a super premium acrylic paint

with Teflon TM protector to provide superior stain resistance and

easy stain removal. It is specially formulated with Green

ingredients to limit air pollutants and other environmental impact. It has extremely low odour during application and drying and is ideal for the painting of commercial and residential areas with high

frequency human traffic.

Acrylic polymer emulsion paint for interior use **Type** 

Colour As per color card

**Finish** Soft sheen finish

**Uses** Recommended for all interior masonry surfaces

**Features** New Anti-Spattering Formulation with Teflon <sup>™</sup> protector

Environmentally friendly green interior emulsion

Low VOCs

Extremely low odour during application and drying

Ammonia-free

Alkyl Phenol Ethoxylate (APE) surfactant free, formaldehyde

Non-toxic, does not contain lead, mercury and heavy metals

Excellent stain resistance to common household stains

Good washability

Elegant soft sheen finish

Long lasting colors

Fungus resistant

Alkali resistant

Easy application

Excellent flow and leveling

Excellent coverage and hiding power

Green Label certified product

#### **APPLICATION DATA**

Method Roller or brush

**Theoretical Coverage** 13 m<sup>2</sup> / litre (based on 30 microns DFT)

**Dilution** No dilution is necessary for best performance

### NIPPON ODOUR-LESS EASYWASH

**Surface Preparation** 

Surface must be clean, dry, stable and free from dust, dirt,

oil, grease and other contaminants prior to painting

Treat fungus-growth areas with NIPPON ANTI-FUNGUS SOLUTION. Rinse again with clean water and dry

**Drying Time** : Touch Dry - 30 minutes at 30 °C

Overcoating Time : 2 hours minimum based on normal conditions

Cleaning : Clean all equipment immediately with clean water after use.

Recommended Painting System

1 coat Vinilex 5101 Wall Sealer or Vinilex 2000 Wall

Sealer

2 coats Nippon Odour-less EasyWash

#### **GENERAL INFORMATION**

**Solid Content**: Above 50% by weight (based on white colour)

**Specific Gravity** :  $1.31 \pm 0.03$  kg/litre (based on white colour)

Packing : 1 and 5 litres

Storage : Store in a tightly sealed container in a cool dry place.

**Shelf Life** : Up to 18 months in a tightly sealed container.

**Precaution** : Avoid direct contact with sensitive skin.

Use appropriate protective equipment.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

**Enquiries Contacts**: Customer Service

6265 5355 (Main Line) 6264 1603 (Fax)

www.nipponpaint.com.sg

<sup>\*</sup> VOC (Volatile Organic Compound) content is based on untinted paint only.