

# Safety Data Sheet

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Product Name:</b>	<b>LIQUID NAILS MIRROR ALUMINIUM</b>
<b>Recommended Use:</b>	High strength construction adhesive for bonding to mirror, metal and glass material.
<b>Supplier:</b>	Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd
<b>ABN:</b>	67 000 049 427
<b>Street Address:</b>	1 Gow Street, Padstow, NSW 2211 Australia
<b>Telephone Number:</b>	+61 2 9781 8777
<b>Facsimile:</b>	+61 2 9781 8825
<b>Emergency Telephone:</b>	<b>1 800 033 111 (ALL HOURS)</b>

## 2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

**Poisons Schedule:** None allocated.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Polydimethylsiloxane compounds	-	>60%	-
Pigments	-	<10%	-
Fillers and plasticisers	-	<10%	-
Oxime silane	2224-33-1	<10%	-
Oxime silane	22984-54-9	<10%	R36/38 R43
Amorphous silica	112945-52-5	<10%	-
Organotin catalysts	-	<10%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

### Skin Contact:

Wipe excess material from skin with a clean rag or paper towel (do NOT use solvent to clean skin). Remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

### Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Product Name:** LIQUID NAILS MIRROR ALUMINIUM  
**Substance No:** 00000010763

**Issued:** 25/05/2015  
**Version:** 3

# Safety Data Sheet

**Ingestion:**

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical assistance.

**Medical attention and special treatment:**

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Hazards from combustion products:**

Combustible paste. On burning will emit toxic fumes.

**Precautions for fire fighters and special protective equipment:**

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

**Suitable Extinguishing Media:**

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency procedures:**

If contamination of sewers or waterways has occurred advise local emergency services.

**Methods and materials for containment and clean up:**

SMALL SPILLS: Wipe up with rag or absorbent paper. Any residual material can be cleaned up with mineral turpentine or similar hydrocarbon solvent, or acetone based nail polish remover.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Scrape up excess material before cure. Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

## 7. HANDLING AND STORAGE

**Conditions for safe storage:**

Store in cool place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

**Precautions for safe handling:**

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Silica Amorphous - Precipitated silica: 8hr TWA = 10 mg/m<sup>3</sup>

# Safety Data Sheet

As published by the National Occupational Health and Safety Commission.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

## Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and safety glasses. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been removed from fingertips, nails and cuticles. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Always wash hands before smoking, eating, drinking or using the toilet. FOR CONSUMER USE: Avoid contact with eyes and skin. Wash hands after use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste
<b>Colour:</b>	Clear
<b>Odour:</b>	Mild
<b>Solubility:</b>	Insoluble in water. Uncured material is soluble in organic solvents. No solvent known for cured sealant.
<b>Specific Gravity:</b>	1.03 @ 20°C
<b>Relative Vapour Density (air=1):</b>	Not available
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	Not available
<b>Flammability Limits (%):</b>	Not available
<b>Autoignition Temperature (°C):</b>	Not available
<b>% Volatile by Volume:</b>	< 10
<b>Solubility in water (g/L):</b>	Insoluble
<b>Melting Point/Range (°C):</b>	Not applicable
<b>Boiling Point/Range (°C):</b>	Not available
<b>Decomposition Point (°C):</b>	>200
<b>pH:</b>	Not applicable
<b>Viscosity:</b>	Not available
<b>Evaporation Rate:</b>	Not available

**Product Name:** LIQUID NAILS MIRROR ALUMINIUM  
**Substance No:** 000000010763

**Issued:** 25/05/2015  
**Version:** 3

# Safety Data Sheet

## 10. STABILITY AND REACTIVITY

<b>Chemical stability:</b>	Stable under normal conditions of use.
<b>Conditions to avoid:</b>	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
<b>Incompatible materials:</b>	Incompatible with oxidising agents.
<b>Hazardous decomposition products:</b>	Oxides of carbon.
<b>Hazardous reactions:</b>	Hazardous polymerisation will not occur.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	Swallowing may result in irritation to the mouth and throat. No adverse effects expected after swallowing cured (solvent free) sealant.
<b>Eye contact:</b>	May be an eye irritant.
<b>Skin contact:</b>	Repeated or prolonged skin contact may lead to irritation. Methyl ethyl ketoxime (liberated during application and setting) is a skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis in sensitive individuals. Cured sealant (solvent free) is not expected to be a skin irritant.
<b>Inhalation:</b>	Methyl ethyl ketoxime is liberated during application and setting. Material may be irritant to the mucous membranes of the respiratory tract (airways).

### Long Term Effects:

No information available for the product.

**Toxicological Data:** No LD50 data available for the product. However, for methyl ethyl ketoxime, released during sealant cure (1):

Oral LD50 (rat): 930 mg/kg

For methyl ethyl ketoxime:

Negative in IN VITRO and IN VIVO genotoxicity assays. Animal studies have shown that this chemical does not cause reproductive or developmental toxicity. Four week inhalation studies in the rat produced a NOEL (for CNS effects) of 714 ppm and NOEL (for blood effects) of 283 ppm. Lifetime inhalation studies in rats and mice have observed changes to liver and nasal tissue (degeneration of olfactory epithelium). Nasal tissue changes were concentration dependant. Recent lifetime inhalation studies have shown statistically significant increase in liver tumours in male rats and male mice at 375 ppm. No tumours were present at lower concentration rates (15 and 75 ppm) or in female rats or mice at any concentration tested. Liver tumour incidence is relatively more common in rodents than humans. At current estimated exposure levels it is not anticipated that methyl ethyl ketoxime represents a carcinogenic risk to humans, however further testing is currently underway to assess the relevance of the above data to humans.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Avoid contaminating waterways.
--------------------	--------------------------------

**Product Name:** LIQUID NAILS MIRROR ALUMINIUM  
**Substance No:** 000000010763

**Issued:** 25/05/2015  
**Version:** 3

# Safety Data Sheet

## 13. DISPOSAL CONSIDERATIONS

**Disposal methods:**

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

## 14. TRANSPORT INFORMATION

**Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

**Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

**Air Transport**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

**Classification:** Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

**Poisons Schedule:** None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

(1) 2006.

Supplier Material Safety Data Sheet;

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)

Fax: 1300 555 305 (Australia wide)

Phone: 0800 735 539 (New Zealand)

Fax: 0800 804 583 (New Zealand)

**Reason(s) for Issue:**

Revised Primary SDS

Alignment to HSNO requirements

# Safety Data Sheet

This safety data sheet has been prepared by SH&E Shared Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.