



ACRYLIC PRIMER

WATER BASED ACRYLIC PRIMER

DESCRIPTION

Davco Acrylic Primer is used as a primer, sealer and bonding agent to prepare floor surfaces prior to the application of waterproofing membrane and wall coating system.

USES

Reduce dust and increase abrasion resistance of the substrate.

Act as a bonding agent to old floors.

Prime and use as a bonding agent on smooth concrete finishes.

Seal pores on rough porous concrete to eliminate air bubble.

SURFACE PREPARATION

Ensure that surface are dry and clean and free from curing compound or release agents.

No chipping or roughening of surface is required if the condition is stable. Old paint work which are stable can remain.

Any contamination including commercial detergents used for cleaning must be thoroughly rinsed off with plenty of water.

TECHNICAL DATA

Physical Properties

Specific Gravity	1.01
Flash Point	Non Flammable
Drying Time	30 min
Water Resistance	Very Good

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

Sika (Singapore) Pte Ltd.
28 Tuas South Avenue 8 Singapore 637648
Tel: (65) 6861 0632 • Fax: (65) 6862 1172
Email: sales@sg.sika.com
Website: www.sika.com.sg
Online Store: davco-online.com.sg

APPLICATION

Apply Davco Acrylic Primer to clean floor with roller, brush and squeegee. Allow to dry till clear film appears. Primer is dry when all milkiness disappears.

COVERAGE

5 - 10m² per litre depending on the substrate condition.

PACKAGING

Davco Acrylic Primer is available in 20 Ltr containers

SHELF LIFE

Shelf life of up to 12 months from the date of manufacture. Store in a cool place away from direct sunlight. Avoid freezing of the Primer.

HEALTH AND SAFETY

Davco Acrylic Primer is non toxic. In case of excessive skin contact, thoroughly flush with clean water. If ill effects occur, seek medical attention promptly. Refer to safety data sheet.

Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website www.sika.com.sg