

**Seng Fong Paints Pte Ltd**  
**Safety Data Sheet**

**Product Name: Tiger Brand Acetone**

**1. IDENTIFICATION OF THE PREPARATION AND COMPANY**

Intended Use : See Product Data Sheet  
Name of Company : Seng Fong Paints Pte Ltd  
Address : No 38, Kian Teck Road, Singapore 628788  
Telephone : + 65 62640100  
Fax : + 65 62640277

**2. HAZARDS IDENTIFICATION OF THE PREPARATION**

**2.1 Product classification according to SS586 Part 2 and Part 3 (2014).**

**Physical Hazards**

Flammable Liquids Category 2

**Health Hazards**

Serious Eye Damage/Eye Irritation Category 2  
Specific Target Organ Toxicity (Single Exposure) Category 3 (Narcotics Effects)  
Specific Target Organ Toxicity (Repeated Exposure) Category 1 (Central Nervous System, Kidneys, Liver)  
Aspiration Hazard Category 2

**2.2 GHS Label Elements**

**Hazard Pictograms:**



**Signal Word : DANGER**

**Hazard Statements**

H225: Highly flammable vapour and liquid.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H305: May be harmful if swallowed and enters airways.

**Precautionary Statements**

P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233: Keep container tightly closed.  
P240: Ground and bond container and receiving equipment.

**Seng Fong Paints Pte Ltd**  
**Safety Data Sheet**

**Product Name: Tiger Brand Acetone**

- P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P242: Use only non-sparking tools.  
P243: Take action to prevent static discharges.  
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264: Wash hands thoroughly after handling.  
P271: Use only outdoors or in a well ventilated areas.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response Statements**

- P301+P310: If SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.  
P303+P352: If ON SKIN (or hair): Wash with plenty of soap and water.  
P303+P361+P353: If ON Skin (or hair): Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/shower.  
P304+P340: If INHALED: Remove victim to fresh air and keep comfortable for breathing.  
P305+P351+P338: If IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
P308+P313: If exposed or concerned: Get medical advice/attention.  
P312: Call a POISON CENTRE or doctor/physician if you feel unwell.  
P331: Do NOT induce vomiting.  
P332+P313: If skin irritation occurs: Get medical advice/attention.  
P337+P313: If eye irritation persists: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash before reuse.  
P370+P378: In case of fire: Use appropriate media for extinction.

**Storage Statements**

- P403+P235: Store in a well-ventilated place. Keep cool.  
P405: Store locked up.

**Disposal Statements**

- P501: Dispose of contents/container in accordance with local and national regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Ingredient Name</b>	<b>CAS Number</b>	<b>Weight %</b>
Acetone	67-64-1	> 99

**4. FIRST AID MEASURES**

**General**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation**

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

**Seng Fong Paints Pte Ltd**  
**Safety Data Sheet**

---

**Product Name: Tiger Brand Acetone**

---

**Eye Contact**

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

**Skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**

If accidentally swallowed, obtain immediate medical attention. Keep at rest . Do NOT induce vomiting.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media**

Recommended: Alcohol resistant foam, CO2, Powders,

Not to be used: Waterjet

Recommendations: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run-off from fire-fighting to enter drains or water courses.

**6. ACCIDENTAL RELEASE MEASURES**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible adsorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13 ). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

**7. HANDLING AND STORAGE**

**Handling**

Vapours are heavier than air and may spread along floors. Vapor may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

**Preparation may charge electrostatically**

Always use earthing leads when transferring from one container another. Operators should wear anti-static footwear, and floors should be of the conducting type.

**Container Storage**

Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Always keep in containers of same material as the original one. Never use pressure to empty as the container is not a pressure vessel.

**Seng Fong Paints Pte Ltd**  
**Safety Data Sheet**

**Product Name: Tiger Brand Acetone**

**Skin And Eye Contact**

Avoid skin and eye contact. Avoid inhalation of vapor and spray mist.

**Application Areas**

Smoking, eating and drinking should be prohibited in application areas.

For personal protection see Section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapor in all cases. In such circumstances should wear a compressed aired respirator during the spraying process until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

**Storage**

Store in accordance with local rules and legislation. Observe label precautions. Store between 5 and 30°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Engineering Measures: Provide adequate ventilation. Where reasonably practicable this should be achieved by use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentration of particulates and solvent vapor below the PEL, suitable respiratory protection must be worn.

<b><u>Ingredient</u></b>	<b><u>CAS No</u></b>	<b><u>Control Parameters/OEL</u></b>
Acetone	67-64-1	Workplace Safety and Health Act (Singapore, 2/2006) Singapore PEL Long Term: 750 ppm (1780 mg/m <sup>3</sup> ) Singapore PEL Short Term: 1000 ppm (2380 mg/m <sup>3</sup> )

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical State	:	Liquid
Flash point	:	-18°C
Specific gravity at 20°C	:	0.79 g/cm <sup>3</sup> (average value)
Vapor density	:	Heavier than air
Colour	:	See colour card
Flammable in air (% by volume)	:	Lower limit: 2.2; Upper limit: 13.0
Solubility in water	:	Not miscible with water

**10. STABILITY AND REACTIVITY**

Stable under recommended storage and handling conditions. (See Section 7) When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smokes, oxides of nitrogen. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**Seng Fong Paints Pte Ltd**  
**Safety Data Sheet**

**Product Name: Tiger Brand Acetone**

## **11. TOXICOLOGICAL INFORMATION**

There are no data available on the preparation itself. The toxicity of the following ingredients were used to assess the health hazards of the preparation.

### **Acute Toxicity**

<b>Ingredient</b>	<b>Oral LD50</b>	<b>Skin LD50</b>	<b>Inhalation LC50</b>
Acetone	>5000 mg/kg Rat	5000 mg/kg Rabbit	>20 mg/l (4hr) Rat

### **Irritation/Corrosion**

<b>Ingredient</b>	<b>Skin Corrosion/Irritation</b>	<b>Serious Eye Damage/Irritation</b>
Acetone	---	Category 2

### **Respiration/Skin Sensitisation**

Not available

### **Germ Cell Mutagenicity**

Not available

### **Carcinogenicity**

Not available

### **Reproductive Toxicity**

Not available

### **Specific Target Organ Toxicity Following Single Exposure**

<b>Ingredient</b>	<b>Hazard Classification</b>	<b>Remarks</b>
Acetone	Category 3	May cause drowsiness or dizziness.

### **Specific Target Organ Toxicity Following Repeated Exposure**

Not available

### **Aspiration Hazard**

Acetone	Category 2	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
---------	------------	--

## **12. ECOLOGICAL INFORMATION**

There are no data available on the preparation itself. The product should not be allowed to enter drains or water courses. The toxicity of the ingredients were used to assess the environmental hazards of the preparation.

**Seng Fong Paints Pte Ltd**  
**Safety Data Sheet**

**Product Name: Tiger Brand Acetone**

**Toxicity**

<b>Ingredient</b>	<b>Results</b>	<b>Species</b>	<b>Exposure</b>
Acetone	LC50 : 6210 mg/l	Flathead Minnow	96 hrs

**Persistence/Degradability**

<b>Ingredient</b>	<b>Half-life</b>	<b>Photolysis</b>	<b>Biodegradability</b>
Acetone	---	---	90% (28 days)

**Bioaccumulative Potential**

<b>Ingredient</b>	<b>Partition Coefficient</b>	<b>BCF</b>	<b>Potential</b>
Acetone	Log Pow : 0.2	---	Not significantly

**Mobility In Soil**

<b>Ingredient</b>	<b>Remarks</b>
Acetone	If product enters soil, it will be mobile and may contaminate groundwater. Dissolves in water.

**Other Adverse Effects**

Not available.

**13. DISPOSAL CONSIDERATIONS**

Do not allow into drains or water courses. Waste and emptied containers should be disposed of according to the local rules and legislation.

**14. TRANSPORT INFORMATION**

Transport only in accordance with ADR for road, RID for rail and IMDG for sea transport.

**ADR/RID**

UN Number	1090
Proper Shipping Name	Acetone
Class	3
Packing Group	II
Label	3
Hazard Identification No	33

**IMDG**

UN Number	1090
Proper Shipping Name	Acetone
Class	3

**Seng Fong Paints Pte Ltd**  
**Safety Data Sheet**

---

**Product Name: Tiger Brand Acetone**

---

Packing Group	2
Label	3
Emergency Schedules	F-E, S-D

#### **15. REGULATORY INFORMATION**

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: This product is subject to the SDS, labelling, PEL and other requirements in the Acts/Regulations.

#### **16. OTHER INFORMATION**

The information of this SDS is based on the present state of our knowledge. As the users' working conditions are beyond our knowledge and control. The product is not to be used for other purpose than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product: it is not be considered as a guarantee of the products' properties.

**Prepared/Last Amended On: 28-September-2021.**

**Valid for 5 years from above date.**

**This SDS will be amended when necessary based on the latest updates provided by raw material suppliers.**