



Cordless Flashlight  
DML812

Satisfy Professional's Needs

**LXT**

# Long beam distance & High brightness



Beam distance

**640 m**

Luminous flux

**1,250 lm**  
Spot + flood

**18V**  
LITHIUM-ION

**XPT**

# Over 640m Beam Distance & Max 1,250 Lumens

## 4 modes

### Spot



Luminous flux

**600 lm**



**640m**



### Spot + Flood



**1,250 lm**



### Flood



**1,000 lm**



### Strobe



**1,250 lm**



This mode is set by pressing the mode button long for smooth transition from any mode to use for alerting etc.

## Continuous run time (with BL1860B)

Spot	Spot + Flood	Flood	Strobe
10 h	6.0 h	7.5 h	8.5 h

## Accessories

Shoulder Strap  
Part No. GM00002239



## On/off switch

## 4 Mode switch

Press the mode switch to cycle

- ▶ Spot
- ▼ Spot + Flood
- ▼ Flood

## Strobe

Press and hold the mode switch until the appliance turns strobe mode.



## Hook



## Variable-angle head

**90°**



## Luminous flux

Spot + flood

**1,250 lm**

## Beam distance

**640 m**

## Cordless Flashlight

### DML812

<b>Run Time (hrs)</b>	Up to: 10 (Spot, with BL1860B)
<b>Illuminance</b>	at 1m from the light source Spot Mode/ Flood Mode/ Spot-Flood Mode: 71,000/ 520/ 51,000 lx
<b>Luminous Flux</b>	Spot Mode/ Flood Mode/ Spot-Flood Mode: 600/ 1,000/ 1,250 lm
<b>Dimensions (L x W x H)</b>	w/ BL1830B / BL1850B / BL1860B: 313x119x115 mm (12-3/8"x4-11/16"x4-1/2")
<b>Net weight</b>	1.2-1.6 kg (2.6-3.4 lbs)

**Standard Equipment:** Shoulder Strap

The weight may differ depending on the attachment(s), including the battery cartridge.  
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.  
Items of standard equipment and specifications may vary by country or area.

## Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE

PRINTED IN SINGAPORE