



CL – FUNGUS CLEANER

WATER BASED FUNGUS AND ALGAE REMOVER

DESCRIPTION

CL-FUNGUS CLEANER is an inorganic water based fungus and algae remover. Upon contact, the fungus cleaner solution will dissolve and kill the fungus and algae. Her fine chemical allows for deep penetration into the substrate to reach and treat the fungus and algae that have grown within the substrate. CL-Fungus Cleaner has no effect on the substrate being treated and it is also non-toxic.

FIXES

CL-Fungus Cleaner can be applied on various substrates like concrete, plaster, brick, wood etc. But care must be exercised when applying on steel or any metal substrates as it may etch the metal surface. As such, it is advisable to test the effect of the remover on the metal substrate before application and to wash the metal substrate with clean potable water shortly after application.

Substrate with fungus or algae, that is to be painted or the like, are highly recommended to be treated with CL-Fungus Cleaner so as to prevent the fungus or algae that will be buried in the coating to grow out of the paint, thereby prolonging the newness of the painted substrate.

FEATURES

- Effectively kill the fungus / algae
- Allow for deep penetration into the substrate
- Non-Toxic
- Ready to use and simple application
- Can be applied on wet and dry surface
- Will not damage to the substrate

TECHNICAL PROPERTIES

Appearance : Clear to cloudy liquid
Odour : Odourless
Density @28°C : Approx. 1.1 g /ml

SURFACE PREPARATION

No surface preparation as well as pre-washing or scrapping is necessary.

APPLICATION

Shake well before use. **DO NOT DILUTE CL-FUNGUS CLEANER.** Apply CL-Fungus Cleaner directly onto the fungus or algae surface. Area being applied could be easily identified where the surface of fungus or algae will turn dark when contact with CL-Fungus Cleaner. Leave it for about 1 hour, then flush with water using water jet and / or soft brush until surface is clean and not slippery. For thick and stubborn fungus or algae, the application may have to be repeated to achieve the result.

PRECAUTION MEASURES

Keep away from acids, metals, halogen and nitro compounds. Wear rubber glove during application. Avoid breathing the mist. When applying by spraying, the strength and direction of the wind is to be considered.

COVERAGE

Approximately 4 – 5 sq meter per litre depending on substrate condition.

SHELF LIFE

2 years in unopened container.

PACKING

Available in 4 litre bottle and 20 litre pail.



Before Treatment



After Treatment

122010

Disclaimer: Specification are subject to change without notification.



CLP since 1947
HQ/SINGAPORE : CLP INTERNATIONAL PTE LTD
CHIN LEONG CONSTRUCTION SYSTEMS PTE LT
TEL : +65-6265 2788
FAX : +65-6265 1240
Email : chinleong@clp.com.sg

MALAYSIA: CLP CONSTRUCTION SYSTEMS SDN BHD
SELANGOR MALACCA
TEL : +60-3-3176 5099 TEL : +60-6-263 1677
FAX : +60-3-3176 2797 FAX : +60-6-263 1215
Email : clp@clp.com.my

JOHOR
TEL : +60-7-252 5385
FAX : +60-7-252 5391

KEDAH
TEL : +60-4-489 3066
FAX : +60-4-489 1877

PERAK
TEL : +60-5-292 6986 / 6976
FAX : +60-5-292 6936

INDONESIA :
PT RANGALO CLP
TEL : +62-21-581 3951
FAX : +62-21-581 3950
Email : rangalo@cbn.net.id

PT-CLP INDONESIA
TEL : +62-21-2931 5121
FAX : +62-21-2931 5133 / 28
Email : info@clpindo.com

THAILAND:
CLPI (THAILAND) CO LTD
TEL : +66-2769 5633
FAX : +66-2769 5612
Email : clpi@ksc.th.com

VIETNAM :
CLPI VIETNAM CO LTD
TEL : +84-8-3526 1033
FAX : +84-8-3526 1032
Email : sales@clp.com.vn

TAIWAN :
SIHTACO CO LTD
TEL : +886-2-2791 8539
FAX : +886-2-8192 6248
Email : Alice.Lee@sihtaco.com.tw
Michael.Ku@sihtaco.com.tw

HONG KONG :
CHIN LEONG INTERNATIONAL CO LTD
LAMERTON ASIA HOLDING LTD
TEL : +852-2542 2206
FAX : +852-2544 9563
Email : chinleong@chinleong.com.hk

CHINA:
LAMERTON CHEMICAL (SHANGHAI) CO LTD
SHANGHAI
TEL : +86-21-5830 7559
FAX : +86-21-6840 7408

ZHONG SHAN SOUTH ASIA CHEMICAL LTD
ZHONG SHAN
TEL : +86-760-8554 4111
FAX : +86-760-8554 4113