



Cordless Screwdriver DFS250 / DFS251

Satisfy Professional's Needs



for Decking applications (DFS250)



for Self drilling screw applications (DFS251)



2,500 RPM High Torque Push Drive Technology Screwdriver

DFS250 : suitable for decking applications

DFS251: suitable for self drilling screw applications



- Maintenance-free due to no brush
- Energy production is more efficient than brushed DC motor because of no friction loss caused by brushes, enabling to lower amperage for reduced heat production and increased work amount on a single full battery charge.

Best possible tool body for screwdriving

- ergonomically designed to:
- minimize hand fatigue and pain even in long continuous operation.
 - give maximum power thrust.
 - allow for much smoother and easier trigger pull.
 - provide comfortable grip and better control with enlarged non-slip elastomer.

Lock-on button for continuous screwdriving

Powered by 18V Li-ion batteries



with Battery fuel gauge

BL1860B: 18V 6.0Ah	BL1820B: 18V 2.0Ah
BL1850B: 18V 5.0Ah	*BL1815N: 18V 1.5Ah
BL1840B: 18V 4.0Ah	*without Battery fuel gauge
BL1830B: 18V 3.0Ah	



Push Drive Technology

- In lock-on mode, the motor does not rotate under no load to minimize power consumption, and starts rotating at full speed only when screws are inserted into a board.
- With ON/OFF switch



Charger

Fast Charger

DC18RC



Two Port Multi

DC18RD



Charging time (3.0Ah)
22minutes

Four Port Multi

DC18SF



DC18SD



DC18SE
(Automotive)



Cordless Screwdriver DFS250 / DFS251

- Variable Speed
- Reversing
- Built-in Job Light
- Carrying Case

Standard Equipment :

DFS250: Phillips Bit, Magnetic Bit Holder, Belt Clip, Battery, Charger

DFS251: Magnetic Socket Bit, Battery, Charger

	DFS250	DFS251
Capacity	Coarse Thread: 4.5 x 90 mm (3/16" x 3-1/2") Self-Drilling Screw: 6 mm (1/4") Drywall Screw: 5 mm (3/16")	Self-Drilling Screw: 6 mm (1/4") Drywall Screw: 5 mm (3/16") Hex Socket Screw: 6 mm (1/4")
Driving Shank (Hex)	6.35 mm (1/4")	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,500	0 - 2,500
Vibration Level	Screwdriving without Impact: 2.5 m/s ² or less	Screwdriving without Impact: 2.5 m/s ² or less
Sound Pressure Level	72 dB(A)	72 dB(A)
Sound Power Level	N/A dB(A)	N/A dB(A)
Dimensions (L x W x H)	259x79x259mm (10-1/4"x3-1/8"x10-1/4")	237x79x259mm (9-3/8"x3-1/8"x11-1/4")
Net weight	BL1815N: 1.6 kg (3.5 lbs.) BL1860B: 1.8 kg (4.1 lbs.)	BL1815N: 1.5 kg (3.3 lbs.) BL1860B: 1.8 kg (3.9 lbs.)

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : salesadv@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE

Item code : Z-10319

PRINTED IN SINGAPORE