



(Refer to the page 9 for details.)

## Technical Data

Accuracy: Refer to the list of specifications.  
(excluding quantizing error for digital models)  
Resolution\*: 0.01mm or .0005"/0.01mm  
Graduation\*\*: 0.05mm  
Display\*: LCD  
Length standard\*: ABSOLUTE electrostatic capacitance type  
linear encoder  
Max. response speed\*: Unlimited  
Battery\*: SR44 (1 pc.), **938882**  
Battery life\*: Approx. 3.5 years under normal use  
\*Digital models \*\*Analog models

## Function of Digital Model

Origin-set, Zero-setting, Automatic power on/off, Data output, inch/mm conversion (inch/mm models)  
Alarm: Low voltage, Counting value composition error

## Optional Accessory for Digital Model

**959143**: Data hold unit  
**959149**: SPC cable with data switch (1m)  
**959150**: SPC cable with data switch (2m)




# Point Caliper


**SERIES 573, 536 — ABSOLUTE Digimatic and vernier type**

## FEATURES

- Narrow tip jaws fit into very small grooves and tracks, making many previously difficult outside measurements far easier to obtain.
- With depth bar.
- With SPC data output. (series 573)



573-121-20



536-121

## SPECIFICATIONS

Metric Digital model		
Range	Order No.	Accuracy
0 - 150mm	<b>573-121-20</b>	±0.02mm
0 - 200mm	<b>573-125-20</b>	±0.02mm

Inch/Metric Digital model		
Range	Order No.	Accuracy
0 - 6"	<b>573-221-20</b>	±.001"
0 - 8"	<b>573-225-20</b>	±.001"

Metric		
Range	Order No.	Accuracy
0 - 150mm	<b>536-121</b>	±0.05mm

## DIMENSION

