

Seng Fong Paints Pte Ltd

MATERIAL SAFETY DATA SHEET

Product Name : Tiger Brand Thinner 237

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

Intended Use : For Thinning (Diluting) Paints
Name of Company : Seng Fong Paints Pte Ltd
Address : No 38, Kian Teck Road, Singapore 628788
Telephone : + 65 62640100
Fax : + 65 62640277

2. COMPOSITION / INFORMATION ON INGREDIENTS

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Name	CAS-No.	Conc.Range	Symbol	R-Phrases
Toluene	108-88-3	50 - 100%	F, Xi, Xn	R11, R38, R48/20, Repr.Cat.3, R63, R65, R67
Acetone	67-64-1	10 - 25%	F, Xi	R11, R36, R66, R67

See full text of phrases in section 16.

3. HAZARDS IDENTIFICATION OF THE PREPARATION

The substance is classified as dangerous according to Directive 67/548/EEC and its amendments.

High flammable

Possible risk of harm to the unborn child.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful: may cause lung damage if swallowed.

Irritating to eyes and skin.

Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES

General

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

Eye Contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

If accidentally swallowed, obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Recommended

Alcohol resistant foam, CO2, Powders, Water spray

Not to be used

Waterjet

Recommendations

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

Seng Fong Paints Pte Ltd

MATERIAL SAFETY DATA SHEET

Product Name : Tiger Brand Thinner 237

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Avoid breathing vapors. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible adsorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Handling

Vapors are heavier than air and may spread along floors. Vapor may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Additionally, the product should only be used in areas from which all naked lights and others sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Preparation may charge electrostatically

Always use earthing leads when transferring from one container another. Operators should wear anti-static footwear, and floors should be of the conducting type.

Container Storage

Keep container tightly closed. Isolate from sources of heat, sparks and open flame.

No sparking tools should be used.

Always keep in containers of same material as the original one.

Never use pressure to empty : Container is not a pressure vessel.

Avoid skin and eye contact. Avoid inhalation of vapor and spray mist.

Smoking, eating and drinking should be prohibited in application areas.

Skin Contacted

Application areas

For personal protection see Section 8.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapor in all cases. In such circumstances they should wear a compressed aired respirator during the spraying process until such time as the particulates and solvent vapor concentration has fallen below the exposure limits.

Storage

Store in accordance with local rules and legislation. Observe label precautions .

Store between 5 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition .Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. No smoking . Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Measures

: Provide adequate ventilation. Where reasonably practicable this should be achieved by use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentration of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn.

Ingredient

Toluene

Workplace Exposure Limits

EH40-WEL (United Kingdom (UK), 1/2005). Skin

STEL: 574 mg/m³ 15 minute/minutes. Form: All forms

STEL: 150 ppm 15 minute/minutes. Form: All forms

TWA: 191 mg/m³ 8 hour/hours. Form: All forms

TWA: 50 ppm 8 hour/hours. Form: All forms

Acetone

EH40-WEL (United Kingdom (UK), 1/2005). Skin

STEL: 3600 mg/m³ 15 minute/minutes. Form: All forms

STEL: 1500 ppm 15 minute/minutes. Form: All forms

TWA: 1210 mg/m³ 8 hour/hours. Form: All forms

Seng Fong Paints Pte Ltd

MATERIAL SAFETY DATA SHEET

Product Name : Tiger Brand Thinner 237

TWA: 500 ppm 8 hour/hours. Form: All forms

Personal Protection

Respiratory Protection : When workers are facing concentrations above the exposure limit, they must use appropriate certified respirators.

Hand Protection : For prolonged or repeated contact, wear suitable gloves. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye Protection : Use safety eyewear designed to protect against splash of liquids.

Skin Protection : Personal should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state :

Flash point	:	-18°C
Volume Solids	:	0%
Specific gravity at 30 °C	:	0.77 - 0.87 gr/cm ³
Vapor density	:	Heavier than air
Color	:	Water White
Texture	:	Liquid
Flammable in air(% by volume)	:	Lower limit : 1.1; Upper limit : 13.0
Solubility in water	:	Not miscible with water

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions. (See section 7) When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide smokes, oxides of nitrogen.

Keep away from oxidizing agents , Strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself.

Exposure to component solvents vapors concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney , liver and central nervous system. Symptoms and signs include headache : dizziness , fatigue , muscular weakness ,Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. ECOLOGICAL INFORMATION

There are no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses .

Waste and emptied containers should be disposed of according to the local rules and legislation.

14. TRANSPORT INFORMATION

Transport only in accordance with ADR for road , RID for rail and IMDG for sea. transport .

ADR/RID

UN Number

1263

Proper Shipping Name

Paint Related Material

Class

3

Seng Fong Paints Pte Ltd

MATERIAL SAFETY DATA SHEET

Product Name : Tiger Brand Thinner 237

Packing Group II
Label 3
Hazard Identification No 30

IMDG

UN Number 1263
Proper Shipping Name Paint Related Material
Class 3
Packing Group II
Label 3
Emergency Schedules F-E, S-E

15. REGULATORY INFORMATION

In accordance with the Dangerous Preparations Directive 88/379/EEC the product is labeled as follow :

Product is both Harmful (Xn) and Dangerous To The Environment (N).

R phrases
R11 Highly flammable.
R36 Irritating to eyes.
R38 Irritating to skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

S phrases
S21 When using do not smoke.
S23 Do not breathe spray.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.
S60 This material and its container must be disposed of as hazardous waste.
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

16. OTHER INFORMATION

Full text of R phrases appearing in section 2 :

Toluene
R11 Highly flammable.
R38 Irritating to skin.
R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.

Acetone
R11 Highly flammable.
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Full text of Symbol phrases appearing in section 2 :

Seng Fong Paints Pte Ltd

MATERIAL SAFETY DATA SHEET

Product Name : Tiger Brand Thinner 237
F - Highly Flammable
Xi - Irritant
Xn - Harmful

The information of this MSDS is based on the present state of our knowledge. As the users' working conditions are beyond our knowledge and control, the product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product; it is not be considered as a guarantee of the products' properties.

Prepared/Last Amended On: 10-Feb-14
