

TECHNICAL DATA SHEET FOR

NIPPON ODOUR~LESS ANTI-MOULD CEILING WHITE

DESCRIPTION	: Nippon Odour~less Anti-Mould Ceiling White is an environmentally favorable green product formulated with anti-mould properties with a broad spectrum protection against most species of mould. It is formulated for ceilings especially damp areas such as kitchen and bathroom and area around air-conditioners.
TYPE	: Modified Acrylic Emulsion for interior use
COLOUR	: White
FINISH	: Matt
USES	: <ul style="list-style-type: none">• Ideally suited for masonry surfaces, such as cement, plastered walls and fibre boards• Ideal for use on ceiling of hospitals, schools, offices and residential buildings• Good for damp areas such as kitchen and bathroom and area around air-conditioners
FEATURES	: <ul style="list-style-type: none">• Environmentally friendly green emulsion product• Non-toxic, does not contain lead, mercury and heavy metals• Anti-mould properties with a broad spectrum protection against most species of mould• Easy application and touch-up• Minimum roller splatter• Excellent flow and leveling which helps to minimize minor surface imperfections• Excellent coverage and hiding power• Environmentally friendly paint certified under the Singapore Green Labeling Scheme SGL-032 by the Singapore Environmental Council with V.O.C. level less than 25g/L
APPLICATION DATA	
METHOD	: Roller or brush
THEORETICAL COVERAGE	: Approx 9-10 m ² / litre (30 microns DFT)
DILUTION	: No dilution is necessary for best performance
SURFACE PREPARATION	: Ensure surface is clean, dry and stable. Remove loose surface matter and contaminants by appropriate means. Treat fungus growth areas with NIPPON ANTI-FUNGUS SOLUTION.

NIPPON ODOUR~LESS ANTI-MOULD CEILING WHITE

DRYING TIME	:	Surface Dry - 30 minutes at 30 °C Hard Dry - 1 hour at 30 °C
OVERCOATING TIME	:	2 hours based on normal conditions
RECOMMENDED PAINTING SYSTEM	:	1 coat of Nippon Odour-less Sealer 2 coat of Nippon Odour-less Anti-Mould Ceiling White
CLEANING	:	All equipment should be cleaned with water immediately after use.
GENERAL INFORMATION		
SOLID CONTENT	:	48 ± 2% by weight
SPECIFIC GRAVITY	:	1.38 ± 2% kg/litre
PACKING	:	5-litre
STORAGE	:	Store in a tightly sealed container in a cool dry place.
SHELF LIFE	:	Up to 18 months in a tightly sealed container.
PRECAUTION	:	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment. Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details	:	Customer Service 6265 5355 (Main Line) 6264 1603 (Fax) www.nipponpaint.com.sg
------------------------------------	---	--